(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention of the grant of the patent: 09.06.2004 Bulletin 2004/24

(51) Int Cl.7: C08G 61/02

(11)

- (21) Application number: 94113883.6
- (22) Date of filing: 05.09.1994
- (54) A process for producing polymers of alpha,omega-unsaturated conjugated compounds, and high molecular weight conjugated polymers thus obtainable

Verfahren zur Herstellung von Polymeren aus alpha-omega-ungesättigten Verbindungen und die erhaltene hochmolekulare konjugierte Polymere

Procédé de préparation de polymères à partir de composés alpha-oméga-insaturés et polymères conjugués de haut poids moléculaire

- (84) Designated Contracting States: **BE DE FR GB**
- (30) Priority: 14.09.1993 EP 93114780
- (43) Date of publication of application: 22.03.1995 Bulletin 1995/12
- (73) Proprietor: Covion Organic Semiconductors GmbH 65926 Frankfurt (DE)
- (72) Inventors:
 - Gelan, Joanes, Prof. Dr. B-3600 Genk (BE)

- Vanderzande, Dirck, Prof. Dr. B-3850 Nieuwerkerken (BE)
- Louwet, Frank, Dr.
 B-3590 Diepenbeek (BE)
- (74) Representative:
 Luderschmidt, Schüler & Partner GbR
 Patentanwälte
 Industriepark Höchst,
 Gebäude F 821
 65926 Frankfurt (DE)
- (56) References cited: WO-A-91/15534

EP 0 644 217 B

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

10

20

25

30

35

40

45

50

[0001] The present invention relates to a process for producing polymers of α , ω -unsaturated conjugated compounds, in particular of compounds which contain aromatic ring systems. It also relates to high molecular weight polymers obtainable by said process, to high molecular weight conjugated polymers and to electroluminescent devices comprising such polymers. There is an urgent industrial need for large-area solid-state light sources, for a wide range of applications mostly related to display technologies, and there is no fully satisfactory technology at present. Polymer-based electroluminescent devices are very promising and they offer several advantages over conventional, inorganic light-emitting diodes and liquid-crystal displays. These advantages include the availability of the whole color spectrum, the ability to make large-area electroluminescent devices, the ability to make flexible displays, and the high brightness of the luminescence. This is combined with simple processing technology and low fabrication costs. Furthermore, displays of this type do not need backlighting, in contrast to liquid-crystal displays.

[0002] Polymer-based electroluminescent devices are described, e.g., in WO 90/13 148 and EP-A 0 443 861. A typical device as described in WO 90/13 148 is made up of a semiconductor layer in the form of a thin dense polymer film comprising at least one conjugated polymer, a first contact layer in contact with a first surface of the semiconductor layer, and a second contact layer in contact with a second surface of the semiconductor layer, wherein the polymer film of the semiconductor layer has a sufficiently low concentration of extrinsic charge carriers that on applying an electric field between the first and second contact layers across the semiconductor layer so as to render the second contact layer positive relative to the first contact layer charge carriers are injected into the semiconductor layer and radiation is emitted from the semiconductor layer.

[0003] The polymer employed as a semiconductor layer in these devices is conjugated.

[0004] By conjugated polymer is meant a polymer which possesses a delocalized π -electron system along the polymer backbone; the delocalized π -electron system confers semiconducting properties to the polymer and gives it the ability to support positive and/or negative charge carriers with high mobilities. Such polymers are discussed, for example, by R. H. Friend in J. Mol. Elec. 4, (1988) 37.

[0005] Poly(p-phenylene vinylene) [PPV] is utilized as a charge conducting layer in WO 90/13 148, and it is suggested in this document to have substituents on the phenylene ring or to replace phenylene with a fused carbocyclic system or a heterocyclic system. Conductive layers made of poly(aniline) [PAn] and poly(2,5-thienylene vinylene) [PTV] are described in EP-A 0 443 861.

[0006] Highly conjugated polymers, such as PPV or PTV, are generally insoluble and infusible because of the stiffness of their backbone. Consequently they are difficult to process. A solution to this problem is their synthesis via soluble precursor polymers or the use of specifically substituted monomers which lead to soluble, specifically sidechain-substituted conjugated polymers.

[0007] The synthesis via precursor polymers proceeds, for example, according to the so-called Wessling bis-(sulphonium salt) precursor route (R. A. Wessling, J. Polym. Sci., Polym. Symp. 72, (1985) 55.). For example, PPV precursor polymers can be prepared by treating an α , α '-bis(sulfonium chloride)-p-xylene, e.g., α , α '-bis(tetrahydrothiophenium chloride)-p-xylene, with NaOH in water or alcohols as a solvent to yield a sulphonium polyelectrolyte. This precursor polymer is soluble and can be processed, e.g. by spin-coating or film-casting. On heating the precursor polymer, PPV is formed by elimination of tetrahydrothiophene and HCl. Although this is a versatile method for the preparation of a wide range of poly(arylene vinylenes) there are two major drawbacks. Firstly, the polyelectrolyte nature of the precursor makes filtration of the precursor solutions difficult or even imposible. This is a severe restriction for all applications were small insoluble particles, like dust, have to be avoided, e.g. for electroluminescent devices. Secondly, the precursor polymers are thermally and chemically unstable. They have to be stored well below zero degree centigrade to prevent partial elimination leading to an insoluble polymer comprising considerable conjugated segments and they are susceptible to substitution reactions, in particular with the commonly used solvents water and methanol.

The mechanism of the formation of the precursor polymer is believed to proceed via an in situ generation of a true monomer, a p-quinodimethane system. Polymerization reactions of p-quinodimethane systems are well known in the literature (e.g., H. G. Gilch and W. L. Wheelwright, J. Polym. Sci. A1 4, (1966) 1337; R. W. Lenz et al, J. Polym. Sci., Polym. Chem. 26, (1988) 3241; G. M. Brooke and M. F. Woolley, Polymer 34, (1993) 1282).

[0008] Specifically substituted monomers which lead to specific sidechain-substituted conjugated polymers have been used to prepare processable conjugated polymers via a dehydrochlorination reaction with a 1,4-bis(halogenomethyl)benzene as monomer. For example, the preparation of poly(2-methoxy-5(2'-ethyl-hexyloxy)-p-phenylene vinylene) from 2,5-bis(chloromethyl)-1-methoxy-4-(2'-ethyl-hexyloxy)benzene is described in US 5,189,136. Another example is the preparation of poly(2,5-di-n-hexyloxy-p-phenylene vinylene) (W. J. Swatos et al., Polymer Prepr. 31(1), (1990) 505). However, the use of the dehydrohalogenation reaction for the preparation of processable conjugated polymers or precursor polymers thereof is limited to specific compounds, since otherwise insoluble and infusible materials are obtained (see for instance H. H. Hörhold and J. Opfermann, Makromol. Chem. 131, (1970) 105).

[0009] It is known (see for instance W. B. Liang, M. Masse and F. Karasz, Polymer 33, (1992) 3101) that in the

synthesis according to Wessling the yield improves and the resulting polymer has a higher molecular weight if an apolar solvent, e.g. hexane, is added to the aqueous reaction mixture.

[0010] There have been attempts to generalize the precursor-route (see, e.g., F. Louwet, D. Vanderzande and J. Gelan, Synth. Met. 52, (1992) 125) or to adapt it to the synthesis of poly(2,5-heteroarylene vinylenes) (see, e.g., H. J. Geise et al., Synth. Met. 51, (1992) 329).

[0011] However, up to now the materials prepared by these processes have not been fully satisfactory with respect to molecular weight, chemical and thermal stability and processability. A high molecular weight is necessary if the polymers are to have good film forming properties and mechanical stability, and to minimize the end-group concentration, since end-groups are likely to influence adversely properties like electroluminescence.

There is clearly room for improvement of the synthesis of PPV and related compounds.

As there is also a steady demand to develop new materials for use in electroluminescent devices, it was highly desirable to find a general synthetic route to such polymers.

[0012] Surprisingly, it has now been found that high molecular weight precursor polymers which are chemically and thermally stable are obtainable in good yields if the formation of the actual monomer, i.e., the p-xylylene or a derivative thereof, is carried out in specific solvents and is accompanied by the formation of a solid that is essentially insoluble in the reaction medium, and the monomer and polymer are soluble in the reaction medium; if extremely high molecular weights are reached, some precipitation of the high molecular weight material can occur.

[0013] Accordingly, the object of the invention is a process for producing polymers of α,ω -unsaturated conjugated compounds, which comprises reacting a compound of the formula (I),

B-A-C (I)

wherein

20

25

40

45

50

55

B denotes a sp³-hybridized carbon atom carrying at least one hydrogen atom,

- A denotes a conjugated- π -system or a -CH = CH-group, and
- C denotes a carbon atom carrying at least one leaving group,

with a base in a solvent, characterized in that on reaction of the base with the compound of the formula (I) a polymer is formed which is essentially soluble in said solvent, and a solid is formed as a by-product, which is essentially insoluble in said solvent, and that said solvent comprises a compound selected from the group consisting of

a) amides of the general formula (II)

35

$$R^1$$
-CO-NR²R³ (II)

b) urea derivatives of the general formula (III)

$$R^1R^3N$$
-CO-NR $^2R^4$ (III)

c) carbonates of the general formula (IV)

$$R^1O-CO-OR^2$$
 (IV)

d) nitroalkanes of the general formula (V)

$$R^6$$
-NO₂ (V)

e) nitriles of the general formula (VI)

$$R^6$$
-CN (VI)

f) amines of the general formula (VII)

$$R^5_2$$
-N- R^6 (VII)

g) sulfones of the general formula (VIII)

$$R^6$$
- SO_2 - R^6 (VIII)

10

5

h) sulfoxides of the general formula (IX)

$$R^6$$
-SO- R^6 (IX)

15

i) phosphoramides of the general formula (X)

$$((R^6)_2)N)_3 - P = O$$
 (X)

20

i) sulfonates of the general formula (XI)

$$R^6-SO_2-O-R^6$$
 (XI)

25

in which formulae (II) to (XI)

R1, R2, R3, R4 denote, independently of each other, H or a straight chain or branched alkyl group, or R1 and R2

together are - $(CH_2)_2$ -, - $(CH_2)_3$ - or - $(CH_2)_4$ -, and

has the meaning of R1 or is a phenyl group which is unsubstituted or substituted by halogen, methyl

and methoxy groups, and

R6 has the meaning of R5, except H.

35

40

45

50

55

30

[0014] Essentially soluble means that the polymer is soluble in the solvent up to a high molecular weight, preferably up to a molecular weight of at least 1·10⁶ (M_w), however, it is understood that if extremely high molecular weights are reached, some precipitation of the extremely high molecular weight material can occur.

[0015] According to the invention chemically and thermally stable, high molecular weight polymers of high purity and high regularity are obtained in good yield. If the products of the novel process carry groups that undergo elimination to form double bonds, high quality electroluminescent materials can be prepared.

The novel process is generally applicable to all kinds of possible starting materials. Both the starting materials and the final products are stable and easy to process. Possible starting materials for the novel process are compounds of the general formula (I),

wherein

B denotes a sp³-hybridized carbon atom carrying at least one hydrogen atom,

A denotes a conjugated π -system or a -CH = CH-group, and

C denotes a carbon atom carrying at least one electron-accepting group.

[0016] In preferred embodiments A comprises an aromatic system or a heteroaromatic system containing nitrogen, sulfur or oxygen.

[0017] Preferably the precursor monomer of the general formula (I) has the structure (Ia),

$$R^{2} - C - A - C - R^{3}$$

$$H R^{4}$$
(1a)

10

15

20

wherein

R¹, R², R³, R⁴ R⁵,R⁶ are independently -H, -R⁵, -OR⁵, -COOR⁵, NO₂, -NR⁵R⁶, -SR⁵, CN, -SO-R⁵, -SO₂-R⁵, -L, are independently C_1 - C_{20} alkyl, phenyl, which can be mono- or disubstituted by R¹, benzyl, or R⁵ and R⁶ together are -(CH₂)₄- or - (CH₂)₅-, and

L A is CI, Br, I, -O-Tos, -O-Mes, -O-Triflate, -(NR⁵₃)[⊕], -(SR⁵R⁶)[⊕] or -OOC-R⁵, is p-phenylene, 2,6-naphthalenediyl, 1,4-naphthatenediyl, 1,4-anthracenediyl, 2,6-anthracenediyl, 9,10-anthracenediyl, 2,5-thienylene, 2,5-furanediyl, 2,5-pyrroldiyl, 1,3,4-oxadiazol-2,5-diyl, 1,3,4-thiadiazot-2,5-diyl, 1,3-benzo[c]furanediyl, 1,3-benzo[c]pyrroldiyl, 1,3-benzo[c]thienylene, thieno [3,2-b]thiophene-2,5-diyl or pyrrolo[3,2-b]pyrrol-2,5-diyl in which H-atoms on the aromatic rings can be substituted by linear or branched hydrocarbon groups having 1 to 22 carbon atoms, such as methyl, ethyl, propyl, isopropyl, butyl, t-butyl, pentyl, heptyl, octyl, lauryl and octadecyl, and electron-donating groups such as linear or branched alkoxy groups having 1 to 22 carbon atoms, eg. methoxy, ethoxy, propoxy, isopropoxy, butoxy, t-butoxy, pentyloxy, hexyloxy, heptyloxy, octyloxy, lauryloxy or octadecyloxy, or halogen atoms or electron-withdrawing groups such as cyano, nitro or ester groups.

25

30

[0018] Especially preferred aromatic groups A include p-phenylene, mono C₁₋₂₂-alkyl-p-phenylene, mono-C₁₋₂₂-alkoxy-p-phenylene, 2,5-di-C₁₋₂₂-alkyl-p-phenylene, 2,5-di-C₁₋₂₂-alkyl-p-phenylene, 2,5-di-C₁₋₂₂-alkoxy-2,5-thienylene, more specifically monomethyl-p-phenylene, monomethoxy-p-phenylene, 2,5-diethoxy-p-phenylene, 2,5-diethoxy-p-phenylene, 2,5-diethoxy-p-phenylene, 2,5-diethyl-p-phenylene, monobutyl-p-phenylene, monobutyl-p-phenylene, 2,5-dibutoxy-p-phenylene, 2,5-diheptyl-p-phenylene, 2,5-diheptyloxy-p-phenylene, 2,5-distearyl-p-phenylene, 2,5-distearyl-p-phenylene, 2,5-dilauryloxy-p-phenylene, 2,5-distearyl-p-phenylene, 2,5-dictyloxy-p-phenylene, 2,5-di-t-butoxy-p-phenylene, 2,5-dictyl-p-phenylene, 2,5-dibutoxy-p-phenylene, 2,5-diethoxy-p-phenylene, 2,5-dibutoxy-p-phenylene, 2,5-dibutoxy-p-phenylene, 2,5-diheptyloxy-p-phenylene, 2,5-dibutoxy-p-phenylene, 2,5-dibutoxy-p-phe

40

45

50 wherein

A, L, R^1 , R^3 have the meaning given in formula (Ia) in claim 4,

P is -SR⁵, -OR⁵, OH, -Cl, -Br, -SO-R⁵, -SO₂-R⁵, CN or -CO-OR⁵, and is a straight chain or branched C₁ to C₁₂ alkyl, phenyl or benzyl.

55

[0020] The following compounds are examples of further preferred precursor monomers

[0021] The compounds of the formula (I) are known per se from the literature. Synthesis of these compounds is described, for example, in W. B. Liang et al., J. Polym. Sci., Polym. Chem. 28, (1990) 2867; I. Murase et al., Synth.

55

Met. 17, (1987) 639; R. M. Gregorius et al., Macromolecules 25, (1992) 6664; N. Tsuyoshi, EP 044381 A2, F. R. Denton III et al., J. Polym. Sci., Polym. Chem. 30, (1992) 2233.

[0022] It goes without saying that mixtures of different precursor monomers of the formula (I) can also be used, which leads to copolymers.

[0023] The precursor monomer of the general formula (I) is reacted with a base to form the actual monomer of the polymerization (scheme 1, steps 2 and 3). Scheme 1

$$H - B_{solvent} + M^{\oplus} Base^{\theta} \rightleftharpoons B_{solvent}^{\theta} + H - Base + M^{\oplus}$$
 (1)

 $R^{\frac{1}{R^2}} A \xrightarrow{R^4} R^4 + B^{\theta} \longrightarrow R^{\frac{\theta}{2}} A \xrightarrow{R^4} R^4 + H - B \qquad (2)$

With $B^{\theta} = B_{solvent}^{\theta}$ or $Base^{\theta}$

10

20

25

30

35

40

45.

50

55

 $R^{\frac{\theta}{R^2}} \wedge A \xrightarrow{R^4} R^4 \qquad R^{\frac{1}{R^2}} \wedge A \xrightarrow{R^4} \wedge L^{\theta} \qquad (3)$

$$M^{\oplus} + L^{\theta} \rightleftharpoons ML \downarrow \tag{4}$$

[0024] As L^{\odot} is removed from the equilibrium in step 3 by the precipitation (step 4), the equilibrium is displaced to the right and formation of the monomer is increased. This is important for the synthesis of high molecular weight polymers.

If pK_A (solvent) is smaller than pK_A (base), the equilibrium in step 1 lies to right and the deprotonated solvent acts as the actual base.

[0025] In general all kinds of metal bases and ammonium bases can be used; non-charged bases such as amines, like triethylamine or pyridine are also suitable. Classes of metal and ammonium bases are e.g., metal hydrides, such as NaH or KH, metal hydroxides, such as NaOH, LiOH or KOH, metal alkoxides, such as NaOMe or NaOEt, KOtBu, metal amides, such as NaNH₂, NaN(SiMe₃)₂, lithiumdiisopropylamide (LDA), organometal compounds, such as n-BuLi, Grignard reagents, and ammonium hydroxides.


In polar aprotic solvents it is especially advantageous to use metal hydrides as they show no nucleophilic properties. In polar protic solvents it is preferred to use bases with a pK_A larger than the pK_A of the solvent. In this case the solvent is deprotonated and the deprotonated solvent acts as the actual base. This introduces a base equalizing effect. As a consequence the M_w of the polymer will be independent of the base used. The presence of the relatively weak base also reduces possible polymer degradation.

[0026] Generally, the amount of base can vary between 100 and 0.1 equivalents with respect to the monomer precursor. Preferably, 50 to 0.5 equivalents of base with respect to the monomer precursor are used. It is especially preferred to employ 10 to 1 equivalents of base per mol of monomer precursor.

An excess of base usually improves polymer yield and molecular weight, especially when the solubility of the monomer precursor is low. In the case of polar aprotic solvents the excess of base is preferably limited to 10 equivalents per mol of monomer precursor in order to avoid excessive degradation of the polymer.

[0027] The process of the invention is carried out in a solvent comprising at least one compound selected from the group consisting of

a) amides of the general formula (II)



R1-CO-NHR2

(IIa)

wherein the symbols have the same meaning as in formula (II).

[0029] Particularly preferred examples of compounds of the formulae (II) to (XI) include monomethyl formamide (MMF), imidazolidone, pyrrolidone, 1,3-dimethylimidazolidin-2-one, N,N-dimethyl-propylene urea (DPMU), ethylene carbonate, propylene carbonate, nitromethane and nitrobenzene.

[0030] It is also possible to use solvent mixtures. It is preferred to use mixtures of the solvents of the formula (II) to (XI) with weakly polar or non-polar aprotic solvents. For example, mixtures of MMF and dichloromethane can be used.

[0031] The solvent used should be able to dissolve the precursor monomer, the actual monomer and the polymer.

In an aprotic polar solvent the concentration of the initiating species depends on the base strength and the nucleophilic properties of the base used. It is preferable to have a base with low nucleophilic character in these cases.

[0032] When carrying out the process of the invention care has to be taken to choose the precursor monomer, base and solvent in such a way that the salt formed in the reaction of the base with the precursor monomer is essentially insoluble in the selected solvent, while the precursor polymer which forms in the reaction is essentially soluble.

[0033] This can be easily achieved, e.g., by checking the solubility of the salt in the given solvent in a standard handbook on the physical properties of the chemical compounds, such as H. Stephen and T. Stephen, "Solubilities of Inorganic and Organic Compounds", Pergamon Press (1963).

[0034] The precipitation of the salt (ML in scheme 1) from the chosen solvent removes it from the equilibrium (scheme 1 steps 3 and 4) and favors the formation of the actual monomer. For high molecular weights of the polymer the concentrations of the actual monomer should be as high as possible.

This can be achieved by keeping the concentration of ML in the given solvent as low as possible.

[0035] To lower the concentration of ML in the solvent one can, e.g.,

- a) add a weakly polar or non-polar protic solvent, like CH₂Cl₂,
- b) use an excess of base, or-
- c) add a salt which is soluble in the given solvent and which has the same cation as ML (for instance sodium tosylate can be added if the solvent is MMF and ML is NaCl).
- [0036] The temperature of the reaction is chosen as a function of the solubility of the precursor monomer, the actual monomer and the polymer. The highest temperature used should be lower then the degradation temperature of the polymer and the temperature at which the solid phase forms a homogeneous phase with the solvent, and the lowest temperature used should be higher than the temperature limit under which there is no formation of the actual monomer (i.e., the quinodimethane system).
- The temperature can be chosen to tune the molecular weight, in the sense that higher temperatures lead to lower molecular weights and lower polymer yields as a consequence of a higher solubility of the salt ML at higher temperatures.
 - [0037] In general the reaction is carried out between -78°C and 200°C, preferably between -40°C and 120°C, and especially preferably between -20°C and 30°C.
- [0038] Usually the reaction is completed within 24 hours, preferably within 8 hours, more preferably within 3 hours.
 [0039] In general the novel process is carried out in an inert atmosphere, e.g. under nitrogen or argon.
 - [0040] The working up of the polymer forming in the reaction is conducted according to methods well known to anyone skilled in the art. For instance, in the case of polymers that are insoluble in water the polymer can be precipitated by adding water. The crude product which is obtained in this way can be further purified, e.g. by reprecipitation, ex-
- 45 traction or dialysis (see for instance B. Vollmert "Grundriss der Makromolekularen Chemie", Bd. II, E. Vollmert-Verlag (1988)).

[0041] The product of the novel process is a polymer comprising recurring units of the general formula (XII),

50

20

55

$$\begin{bmatrix}
R^{1} & - & R^{3} \\
C & - & A & - & C & - \\
R^{2} & & R^{4}
\end{bmatrix}$$
(XII)

wherein

10

15

20

25

30

35

40

45

50

R¹, R², R³, R⁴ and A have the same meaning as in general formula (I).

[0042] Preferably the precursor polymer of the general formula (XII) has a molecular mass M_w of more than $2 \cdot 10^6$, more preferably from $2 \cdot 10^6$ to $4 \cdot 10^6$.

[0043] Such a polymer is also an object of the invention.

[0044] Preferred polymers of the general formula (XII) are also those having recurring units of the general formula (XIIa)

$$\begin{bmatrix}
P & H \\
C & A & C \\
I & H
\end{bmatrix}$$
(X110)

wherein

P is -SO-R, SO₂-R,

R is a straight chain or branched C₁ to C₁₂ alkyl group, phenyl or benzyl, and

A has the meaning given in formula (la).

[0045] Preferred polymers of the general formula (XIIa) have a molecular mass M_w of more than 1 • 10⁵, preferably more than 1 • 10⁶, particularly preferrably from 1 • 10⁶ to 4 • 10⁶.

[0046] The polymers prepared by the novel process can, e.g., be used as intermediates for producing conjugated polymers, such as PPV.

[0047] Polymers of the general formula (Ia) which contain a group that can undergo 1,2-elimination can be further reacted to yield fully or partly conjugated polymers, such as poly(p-phenylene vinylene). Suitable groups for elimination include sulfoxides, sulfones, alcohols, alkoxides, ammonium salts, sulfonium salts and the like.

Depending on the leaving group present in the precursor polymer the elimination can be carried out, e.g., by thermal treatment or/and under acidic or basic conditions, according to methods known from the literature (see for instance D. A. Halliday et al, Adv. Mater. 5, (1993) 40). The elimination can be carried out before and/or after processing depending on the solubility of the resulting conjugated polymer. For example, the elimination step of precursors of side group solubilized poly(p-phenylene vinylene) such as poly(2,5-dihexyloxy-p-phenylene vinylene), can be performed after processing, while poly(p-phenylene vinylene) has to be processed in the precursor state. The temperature range usually chosen for thermal elimination lies between 80 to 300°C and depends on the nature of the aromatic units, the substituents on the aromatic units, the nature of the eliminating groups and experimental conditions, e.g., quality of an applied vacuum, neutral, acidic or basic environment.

[0048] By employing the polymers of the inventive process conjugated polymers with high molecular weights are obtainable.

[0049] Preferred conjugated polymers that are obtained by the inventive process are those having recurring units of

the general formula (XIII)

$$[-A-CH=CH-] (XIII)$$

wherein

A has the meaning given in formula (la).

[0050] Preferably polymers of the general formula (XIII) have a molecular weight of more than 2 • 10⁶, more preferred 2 • 10⁶ to 4 • 10⁶.

Such polymers are also an object of the invention.

[0051] A further object of the invention is a process for producing conjugated polymers comprising

a) reacting a compound of the general formula (lb)

25

30

35

40

45.

50

55

15

20

wherein

A, L, R¹, R³ have the meaning given in formula (Ia), and

P is -SR⁵, -OR⁵, OH, -Cl, -Br, -SO-R⁵, -SO₂-R⁵, CN, -CO-OR⁵,

 R^5 is a straight chain or branched C_1 to C_{12} alkyl, phenyl, benzyl,

and a base in a solvent comprising a compound selected from the group consisting of

a) amides of the general formula (II)

$$R^1$$
-CO-NR²R³ (II)

b) urea derivatives of the general formula (III)

$$R^1R^3N-CO-NR^2R^4$$
 (III)

c) carbonates of the general formula (IV)

$$R^1O-CO-OR^2$$
 (IV)

d) nitroalkanes of the general formula (V)

$$R^6-NO_2$$
 (V)

e) nitriles of the general formula (VI)

R6-CN (VI) f) amines of the general formula (VII) (VII) g) sulfones of the general formula (VIII) 10 R6-SO2-R6 (VIII) h) sulfoxides of the general formula (IX) 15 R6-SO-R6 (IX) i) phosphoramides of the general formula (X) 20 $((R^6)_2)N)_3-P=0$ (X) i) sulfonates of the general formula (XI) 25 (XI) in which formulae (II) to (XI) 30 denote, independently of each other, H or a straight chain or branched alkyl group, or R1 and R1, R2, R3 and R4 $\rm R^2$ together are -(CH_2)_2^-, -(CH_2)_3^- or -(CH_2)_4^-, and has the meaning of R1 or is a phenyl group which is unsubstituted or substituted by halogen, R⁵ methyl and methoxy groups, 35 R6 has the meaning of R5, except H. whereupon a polymer is formed, which is essentially soluble in said solvent, and a solid by-product is formed, which is essentially insoluble in said solvent, 40 b) optionally isolating said polymer, and c) treating said polymer under conditions effecting elimination of H-P (P having the meaning given in formula (Ib)), thus forming a conjugated polymer. 45 [0052] Conjugated in the sense of the invention does not necessarily mean that the polymer is fully conjugated; however, substantial parts of the polymer have to be conjugated. [0053] Conjugated polymers prepared according to the invention can be used as electroluminescent layers and/or charge transport layers in electroluminescent devices (e.g., WO 90/13148 and EP-A-0 443 861). The polymers can also be used, after doping, for conductive polymer applications, e.g., antistatic surfaces and electromagnetic shielding. 50 Further, the polymers are useful for high temperature applications, e.g., thermally stable coatings. [0054] The invention is illustrated but not limited by the examples which follow. Examples 55 A. Starting Materials

[0055] α, α' -Dichloro-p-xylene, thiophenol, n-butanethiol, dichloromethane and potassium tert.-butoxid were used as

purchased from Janssen Chimica. Sodium hydride, stabilized as an emulsion in higher alkanes, was purified by washing with n-hexane and dried under vacuum. Tetrahydrofuran (THF), N-methylpyrrolidone (NMP) and N-methylformamide (MMF) were dried and purified as described in the literature.

B. Monomer Synthesis

20

55

Example 1: α -Chloro- α '-phenylsulfinyl-p-xylene (1a)

[0056] In a 250 ml dropping funnel 3.8 ml (0.0378 mol) thiophenol was dissolved in 100 ml dry THF and 0.91 g (0.0378 mol) NaH was slowly added. Sodium thiophenolate formed a suspension in the THF. This suspension was added dropwise at 25°C and under vigorous stirring to 33.08 g (0.189 mol) α , α '-dichloro-p-xylene dissolved in 150 ml THF. The reaction mixture was allowed to stand overnight, after which 100 ml water was added. The sulfide and the excess α , α '-dichloro-p-xylene were extracted with 4 x 50 ml CHCl₃. The organic layer was dried over MgSO₄. After filtration, the solvent was evaporated and the resulting crude material was used in the following oxidation step.

[0057] In a 1 I flask the excess α , α '-dichloro-p-xylene, the synthesized α -chloro- α '-phenylsulfide-p-xylene (theor. 0.037 mol) and 0.6 g (3.7 • 10⁻⁴ mol) TeO₂ were dissolved in 450 ml MeOH. 8.60 ml (0.076 mol) H₂O₂ (30 wt%) was added dropwise to the well-stirred solution. After 4 hours 100 ml water was added. The aqueous layer was extracted with CHCl₃, and the extract was dried over MgSO₄ and evaporated. (1a) was separated from α , α '-dichloro-p-xylene by use of a silica column (1 g crude product on 10 g silica, with CHCl₃ as an eluent). After recrystallization from hexane/ toluene, bright white crystals were obtained. Yield: 5.5 g (55 %)

Example 2: α -Chloro- α '-phenylsulfonyl-p-xylene (1b)

[0058] 27.61 g (0.104 mol) (1a) was dissolved in 400 ml CH_2Cl_2 . This solution was added dropwise to an ice-cooled solution of 36.03 g (0.208 mol) 3-chloroperbenzoic acid in 600 ml CH_2Cl_2 and 33.61 g (0.375 mol) NaHCO₃ in 200 ml H_2O . After the addition of (1a) the mixture was allowed to warm up to room temperature, and this was followed by another 2 hours' stirring. The reaction mixture was then poured into 500 ml 5 % Na_2CO_3 solution. The organic layer was washed with 500 ml 5 % $Na_2S_2O_3$ solution. The CH_2Cl_2 was dried over $MgSO_4$ and evaporated. The precipitate was purified by recrystallization from hexane/toluene. Yield: 26.65 g (91 %); m.p. = 170.3 - 170.9°C (dec.)

Example 3: α -Chloro- α '-n-butylsulfinyl-p-xylene (1c)

[0059] A mixture of 99.7 g (0.57 mol) α , α '-dichloro-p-xylene in 1000 ml toluene (benzene), 60 g NaOH (1.5 mol) in 1000 ml H₂O and 2.5 g of a phase transfer catalyst Aliquat 336 was stirred vigorously at ambient temperature. To this mixture a solution of 30.5 ml butanethiol (0.285 mol) in 300 ml toluene (benzene) was added dropwise over a period of 24 hours. The mixture was stirred for another 2 hours. The organic layer was separated off, washed with water, dried over MgSO₄, filtered and evaporated on a rotary evaporator to give whitish-yellow crystals. The crystals (a mixture of α , α '-dichloro-p-xylene and α -chloro- α '-n-butylsulfide-p-xylene) were dried to constant weight under vacuum. This crude material was used without further purification in the following oxidation step.

4.614 g of a catalyst, TeO_2 , (2.891 • 10^{-2} mol) was added to a solution of the crude material in 1200 ml of MeOH. 64.66 ml (0.5702 mol) of a hydrogen peroxide solution (35 wt% solution in water) was added dropwise under nitrogen, with vigorous stirring. The reaction mixture was stirred vigorously at room temperature until a slight over-oxidation was detectable by thin layer chromotography. The reaction was quenched by adding 800 ml of a saturated NaCl solution. The water layer was extracted once with 600 ml CHCl₃ and 2 twice with 400 ml CHCl₃. The combined CHCl₃ layers were dried over MgSO₄, filtered and evaporated on a rotary evaporator to give white crystals (a mixture of α , α '-dichlorop-xylene and α -chloro- α '-n-butylsulfinyl-p-xylene). The two products were separated by column chromatography (silica / CHCl₃). α , α '-Dichloro-p-xylene can be reused after recrystallization from toluene. α -Chloro- α '-n-butylsulfinyl-p-xylene was recrystallized from a mixture of hexane/CH₂Cl₂, washed with ice cold diethyl ether and dried under vacuum. Yield: 53.7 g (77 %) of white crystals; m.p. 111.9-113.0°C.

Example 4: α -Chloro- α '-n-butylsulfonyl-p-xylene (1d)

[0060] A mixture of 42 g 3-chloroperoxybenzoic acid (0.134 mol; 50-60 %, stabilized with 3-chlorobenzoic acid and water) in 500 ml $\rm CH_2Cl_2$ and 50.25 g (0.598 mol) $\rm NaHCO_3$ in 300 ml $\rm H_2O$ was stirred vigorously and cooled to 0°C. A solution of 25 g (0.102 mol) α -chloro- α -n-butylsulfinyl-p-xylene in 125 ml $\rm CH_2Cl_2$ was added dropwise. The mixture was allowed to warm up to room temperature and was stirred for another 3 hours. The organic layer was separated off, washed with 1250 ml of a 5 % $\rm Na_2CO_3$ solution, treated with 1250 ml of a 5 % $\rm Na_2CO_3$ solution. The organic layer was dried over MgSO₄, filtered and evaporated on a

rotary evaporator to give whitish-yellow crystals. The crystals were recrystallized from a mixture of hexane/CH₂Cl₂, washed with ice-cold diethyl ether and dried under vacuum. Yield: 23.4 g (88 %) of white needles were obtained; m. p. 123.1-124.0°C.

C. Polymerization

10

15

20

25

30

35

40

45

50

55

Example 5: Polymerisation of α-chloro-α'-n-butylsulfonyl-p-xylene in N-methylformamide (MMF)

[0061] 521 mg (1.998 • 10^{-3} mol) of α -chloro- α '-n-butylsulfonyl-p-xylene were dissolved in 20 ml dry MMF and the solution was flushed with dry nitrogen under vigorous stirring for 2 hours. 225 mg (2.005 • 10^{-3} mol) KOtBu was added. After 5 to 10 min the solution became turbid and a solid (KCl) precipitated. The polymerization was allowed to proceed at room temperature for 1 hour (still under a constant stream of nitrogen). Then the reaction mixture was poured into 200 ml H_2O and neutralized with dilute HCl. The white precipitate was filtered off, washed thoroughly with water and dissolved in 50 ml CHCl₃. The organic layer was separated from residual H_2O and concentrated on a rotary evaporator to 5 ml. The polymer was precipitated in 200 ml diethyl ether, filtered off and dried under vacuum. Yield: 121 mg (27 %); molecular masses according to GPC (polystyrene standards):

$$M_w = 16.4 \cdot 10^5$$
; $M_n = 250 \cdot 10^3$; $M_w/M_0^* = 6.7$

Monomodal dispersity

Example 6: Polymerization of α -chloro- α '-n-butylsulfonyl-p-xylene in MMF / CH_2Cl_2 (80 : 20)

[0062] 521 mg (1.998 • 10^{-3} mol) of α -chloro- α -n-butylsulfonyl-p-xylene were dissolved in a mixture of 16 ml dry MMF and 4 ml CH₂Cl₂. The solution was flushed for 2 hours with dry nitrogen under vigorous stirring. The nitrogen stream that left the flask was cooled with a mixture of dry ice/isopropanol to condense the evaporated CH₂Cl₂. 225 mg (2.005 • 10^{-3} mol) KOtBu was added. After 5 to 10 min the solution became turbid and a solid (KCl) precipitated. The polymerization was allowed to proceed at room temperature for 1 hour. The solution was poured into 100 ml CH₂Cl₂, and washed 3 times with 50 ml slightly acidic water (pH = 3 to 4) and 3 times with 100 ml water. The organic layer was concentrated on a rotary evaporator to 5 ml. The white polymer was precipitated in 200 ml diethyl ether, filtered off and dried under vacuum. Yield: 157 mg (35 %); molecular masses according to GPC (polystyrene standards):

$$M_w = 21.0 \cdot 10^5$$
; $M_p = 510 \cdot 10^3$; $M_w/M_p^* = 4.1$

* Monomodal dispersity

Example 7: Polymerization of α-chloro-α'-n-butylsulfinyl-p-xylene in N-methylpyrrolidone (NMP)

[0063] 1 g ($4.08 \cdot 10^{-3}$ mol) of α -chloro- α '-n-butylsulfinyl-p-xylene was dissolved in 20.4 ml dry NMP. The solution was flushed with a stream of dry nitrogen under vigorous stirring for 1 hour. After cooling the polymerization vessel to -20°C, 98.0 mg ($4.08 \cdot 10^{-3}$ mol) NaH was added all at once. After 5 to 10 min the solution became turbid and a solid (NaCl) precipitated. The polymerization was allowed to proceed for 1 hour. Then the mixture was poured into 200 ml ice-water and the aqueous solution was neutralized with dilute HCl. The precipitate was filtered off, washed with water and redissolved in CHCl₃. The CHCl₃ layer was dried, concentrated and added dropwise to 200 ml cold diethyl ether. The precipitate was filtered off, washed with diethyl ether and dried under vacuum at room temperature. To remove oligomers formed during polymerization the concentrated CHCl₃ layer can be added dropwise to a 10-fold excess of THF/diethyl ether (50 : 50). Yield: 306 mg (36 %); molecular masses according to GPC (in NMP, polystyrene standards):

$$M_w 300 \cdot 10^3$$
; $M_p = 70 \cdot 10^3$; $M_w/M_p^* = 4.3$

Monomodal dispersity

Comparative Example 1: Polymerization of α -chloro- α '-n-butylsulfinyl-p-xylene in tetrahydrofurane (THF) with NaH

[0064] 1 g (4.08 • 10⁻³ mol) α -chloro- α '-n-butylsulfinyl-p-xylene dissolved in 50 ml dry THF. The solution was flushed

with stream of dry nitrogen for 1 hour, under vigorous stirring. The nitrogen stream that left the flask was cooled with a mixture of dry ice/isopropanol to condense the evaporated THF. 98.0 mg (4.08 • 10⁻³ mol) NaH was added all at once. After 1 hour, 2 hours, and 5 hours respectively, a sample (2.5 ml) of the polymerization mixture was poured into 25 ml ice-water. The precipitate was filtered off, washed with water and dried. GPC indicated that noticeable polymerization occurs only after 5 hours. After 24 hours the remaining reaction mixture was poured into 250 ml ice-water and the aqueous solution was neutralized with dilute HCl. The precipitate was filtered off, washed with water and redissolved in CHCl₃. The CHCl₃ layer was dried, concentrated and added dropwise to 200 ml cold diethyl ether. The precipitate was filtered off, washed with diethyl ether and dried under vacuum at room temperature. Yield: 202 mg (28 %); molecular masses according to GPC (in NMP, polystyrene standards):

$$M_w = 22 \cdot 10^3$$
; $M_n = 5.2 \cdot 10^3$; $M_w/M_n^* = 4.2$

Monomodal dispersity

10

15

20

25

Comparative Example 2: Polymerization of α -chloro- α -n-butylsulfinyl-p-xylene in tetrahydrofurane (THF) with KOtBu

[0065] 1 g (4.08 • 10⁻³ mol) of α-chloro-α'-n-butylsulfinyl-p-xylene was dissolved in 50 ml dry THF. The solution was flushed with a stream of dry nitrogen for 1 hour, under vigorous stirring. The nitrogen stream that left the flask was cooled with a mixture of dry ice/isopropanol to condense the evaporated THF. 458.0 mg (4.08 •10⁻³ mol) KOtBu was added all at once. After 24 hours the reaction mixture was poured into 300 ml ice-water and the aqueous solution was neutralized with dilute HCl. The precipitate was filtered off, washed with water and redissolved in CHCl₃-layer was dried, concentrated and added dropwise to 200 ml cold diethyl ether. The precipitate was filtered off, washed with diethyl ether and dried under vacuum at room temperature. Yield: 212 mg (25 %); molecular masses according to GPC (in NMP, polystyrene standards):

$$M_w = 16 \cdot 10^3$$
; $M_p 5.0 \cdot 10^3$; $M_w/M_p^* = 3.2$

Monomodal dispersity

D. Polymer Conversion

Example 8: Conversion to poly(p-phenylene vinylene), PPV

[0066] The PPV-precursor polymer obtained as described in Example 7 was spin-cast from chloroform solutions to give a homogeneous, colorless and transparent film. The chloroform solution was easily filterable through a µm-filter. The film showed no yellowing when stored for several weeks in a normal atmosphere at room temperature. The precursor film was converted by thermal treatment (280°C/4h/10⁻⁵mbar) to a homogeneous, yellow and transparent PPV-film, which was highly fluorescent (yellow-green). The infrared spectrum of the PPV-film accorded with those known from the literature (e.g., D. D. C. Bradley, J. Phys., Appl. Phys. 20, (1987) 1389).

Claims

45

50

55

1. A process for producing polymers of α, ω -unsaturated conjugated compounds, which comprises reacting a precursor monomer of the formula (Ia) is employed

$$R^{2}$$
— C — C — R^{3} (1a)

wherein

5		R¹ and R² are independently, -H, -R⁵, -OR⁵, -COOR⁵, NO₂, -NR⁵R⁶, -SR⁵, CN, -SO-R⁵, -SO₂-or R⁵, are independently, -H, -R⁵, -OR⁵, -COOR⁵, NO₂, -NR⁵R⁶, -SR⁵, CN, -SO-R⁵, -SO₂-R⁵, or -L, are independently C₁-C₂₀ alkyl, phenyl, which can be mono- or disubstituted by R¹, or benzyl, or R⁵ and R⁶ together are -(CH₂)₄- or -(CH₂)₅-, and L is, Cl, Br, I, -O-Tos, -O-Mes, -O-Triffate, -(NR⁵₃)⊕, -(SR⁵R⁶)⊕ or -OOC-R⁵, is p-phenylene, 2,6-naphthalenediyl, 1,4-naphthalenediyl, 1,4-anthracenediyl, 2,6-anthracenediyl, 9,10-anthracenediyl, 2,5-thienylene, 2,5-furanediyl, 2,5-pyrroldiyl, 1,3-benzo[c]thienylene, thieno [3,2-b]thiophene-2,5-diyl or pyrrolo[3,2-b]pyrrol-2,5-diyl in which H-atoms on the aromatic rings can be substituted by linear or branched hydrocarbon groups having 1 to 22 carbon atoms and linear or branched alkoxy groups having 1 to 22 carbon atoms, halogen atoms or cyano, nitro or ester groups,					
15		with a base in a solvent, said process being characterized in that on reaction of the base with the compound of the formula (Ia) a polymer is formed which is essentially soluble in said solvent and a solid is formed as a byproduct, which is essentially insoluble in said solvent and that the solvent comprises a compound selected from the group consisting of					
		a) amide	es of the general formula (II)				
20			R ¹ -CO-NR ² R ³	(11)			
		b) urea	derivatives of the general formula (III)				
25			R¹R³N-CO-NR²R⁴	(III)			
		c) carbo	onates of the general formula (IV)				
30			R ¹ O-CO-OR ²	. (IV)			
		d) nitroa	alkanes of the general formula (V)				
35			R ⁶ -NO ₂	(V)			
	e) nitriles of the general formula (VI)						
40			R ⁶ -CN	(VI)			
45		f) amine	es of the general formula (VII)				
			R ⁵ ₂ -N-R ⁶	(VII)			
		g) sulfor	nes of the general formula (VIII)				
50			R ⁶ -SO₂R ⁶	(VIII)			
		h) sulfo	xides of the general formula (IX)				
55			R ⁶ -SO-R ⁶	(IX)			

i) phosphoramides of the general formula (X)

$$((R^6)_2)N)_3$$
-P=O (X)

j) sulfonates of the general formula (XI)

$$R^6-SO_2-O-R^6$$
 (XI)

in which formulae (II) to (XI).

- R¹, R², R³ and R⁴ denote, independently of each other, H or a straight chain or branched alkyl group, or R¹ and R² together are -(CH₂)₂-, -(CH₂)₃- or -(CH₂)₄-, and
- has the meaning of R¹ or is a phenyl group or a phenyl group substituted by halogen, methyl and methoxy groups,
- R⁶ has the meaning of R⁵, except H.
- 2. A process as claimed in claim 1, characterized in that the solvent comprises a compound of the formula (IIa),

wherein

10

15

20

25

30

35

40

45.

50

55

R¹ and R² have the same meaning as in formula (II) in claim 1.

- 3. A process as claimed in claim 1 or 2, being **characterized in that** a salt which is soluble in the solvent and which has the same cation as the base, is added to the reaction.
- 4. A polymer comprising recurring units of the general formula (XII)

$$\begin{bmatrix} R^{1} & R^{3} \\ I & I \\ C - A - C - I \\ R^{2} & R^{4} \end{bmatrix}$$
 (X11)

wherein


 R^1 , R^2 , R^3 and R^4 have the same meaning as in formula (Ia) in claim 1, having a molecular weight M_w of more than 2 \bullet 10⁶.

5. A polymer as claimed in claim 4 comprising recurring units of the general formula (XIIa)

$$\begin{bmatrix}
P & H \\
C & A & C
\end{bmatrix}$$
(XIIa)

wherein

- P is -SO-R⁵, SO₂-R⁵, SR⁵, OR⁵, CI, Br, CN or -CO-OR⁵,
- R5 is a straight chain or branched C₁ to C₁₂ alkyl group, phenyl or benzyl, and
- A has the meaning given in formula (la) in claim 1,
- 5 having a molecular weight M_w of more than $2 \cdot 10^6$.
 - 6. Use of a polymer, obtainable by a process as claimed in one or more of the claims 1 to 3 as an intermediate for producing electroluminescent materials.
- 7. A process for producing conjugated polymers which comprises
 - a) reacting a compound of the general formula (lb)



wherein

15

20

25

30

35

45

50

55

A, L, R¹ and R³ have the meaning given in formula (Ia) in claim 1,

P is $-SR^5$, $-OR^5$, OH, -CI, -Br, $-SO-R^5$, $-SO_2'-R^5$, CN or $-CO-OR^5$, and

R⁵ is straight chain or branched C₁ to C₁₂ alkyl, phenyl, benzyl,

and a base, in a solvent comprising a compound selected from the group consisting of

a) amides of the general formula (II)

$$R^1$$
-CO-NR $^2R^3$ (II)

b) urea derivatives of the general formula (III)

$$R^1R^3N$$
-CO-NR $^2R^4$ (III)

c) carbonates of the general formula (IV)

$$R^1O-CO-OR^2$$
 (IV)

d) nitroalkanes of the general formula (V)

$$R^6$$
-NO₂ (V)

e) nitriles of the general formula (VI)

f) amines of the general formula (VII)

			•	R ⁵ ₂ -N-R ⁶		. (VII)		
5		g) sulfones of	the general formula	a (VIII)				
J				R ⁶ -SO₂-R ⁶		(VIII)		
10		h) sulfoxides o	of the general formu	ıla (IX)				
		·		R ⁶ SO-R ⁶		(IX)		
15	i) phosphoramides of the general formula (X)							
				$((R^6)_2)N)_3$ -P=O		(X)		
20		j) sulfonates of	f the general formu	la (XI)				
. •				R ⁶ -SO ₂ -O-R ⁶		(XI)		
25		in which formulae ((II) to (XI)					
		R ¹ , R ² , R ³ and R ⁴	and R ² together	dently of each other, H, a straight are -(CH ₂) ₂ -,-(CH ₂) ₃ - or -(CH ₂) ₄ -,	and			
30		R⁵ R ⁶	methyl and meth	g of R ¹ or is a phenyl group or a p noxy groups, g of R ⁵ , except H.	onenyi group substiti	ited by nalogen,		
			ner is formed, which y insoluble in said s	n is essentially soluble in said solve	ent, and a solid by-p	roduct is formed,		
35			ng said polymer, ar					
			ymer under condition	ons effecting elimination of HP (P	having the meaning	given in formula		
40	8.	A polymer comprising r	repeating units of th	ne general formula (XIII),				
				[- A - CH = CH -]		(XIII)		
45		wherein A has the meaning give	en in formula (Ia) in	claim 1, having a molecular mass	s M _w of more than 2	♦ 10 ⁶ .		
50	9.	Electroluminescent dev	vice, comprising a p	polymer obtainable by a process a	s claimed in claim 7	or a polymer as		

Patentansprüche

50

1. Verfahren zur Herstellung von Polymeren α , ω -ungesättigter, konjugierter Verbindungen, umfassend die Umsetzung eines Monomervorläufers der Formel (Ia)

$$R^{2} - C - A - C - R^{3}$$

$$H = R^{4}$$
(1a)

10 in der

Α

15

20

25

30

35

40

45

50

55

R¹ und R², unabhängig voneinander, -H, -R⁵, -OR⁵, -COOR⁵, NO₂, -NR⁵R⁶, -SR⁵, CN, -SO-R⁵, -SO₂- oder R⁵ sind;

R³ und R⁴, unabhängig voneinander, -H, -R⁵, -OR⁵, -COOR⁵, NO₂, -NR⁵R⁶, -SR⁵, CN, -SO-R⁵, -SO₂-R⁵ oder -L sind;

R⁵ und R⁶, unabhängig voneinander, C₁-C₂₀-Alkyl, Phenyl, das einfach oder zweifach durch R¹ substituiert sein kann, oder Benzyl sind, oder in der R⁵ und R⁶ zusammen -(CH₂)₄- oder -(CH₂)₅- sind; und

L CI, Br, I, -O-Tos, -O-Mes, -O-Triflat, -(NR53)[®], -(SR5R6)[®] oder -OOC-R5 ist;

p-Phenylen, 2,6-Naphthalindiyl, 1,4-Naphthalindiyl, 1,4-Anthracendiyl, 2,6-Anthracendiyl, 9,10-Anthracendiyl, 2,5-Thienylen, 2,5-Furandiyl, 2,5-Pyrroldiyl, 1,3,4-Oxdiazol-2,5-diyl, 1,3,4-Thiadiazol-2,5-diyl, 1,3-Benzo[c]furandiyl, 1,3-Benzo[c]pyrroldiyl, 1,3-Benzo[c]thienylen, Thieno[3,2-b]thiophen-2,5-diyl oder Pyrrolo[3,2-b]pyrrol-2,5-diyl ist, wobei Wasserstoffatome an den aromatischen Ringen durch lineare oder verzweigte Kohlenwasserstoffgruppen mit 1 bis 22 Kohlenstoffatomen und durch lineare oder verzweigte Alkoxygruppen mit 1 bis 22 Kohlenstoffatomen, sowie durch Halogenatome oder Cyano-, Nitro- oder Estergruppen substituiert sein können;

mit einer Base in einem Lösungsmittel, wobei der genannte Prozeß dadurch gekennzeichnet ist, daß bei der Umsetzung der Base mit der Verbindung der Formel (Ia) ein in dem genannten Lösungsmittel weitgehend lösliches Polymer und als Nebenprodukt ein in dem genannten Lösungsmittel weitgehend unlöslicher Feststoff entstehen, und daß das Lösungsmittel eine aus der folgenden Gruppe ausgewählte Verbindung ist:

a) Amide der allgemeinen Formel (II)

$$R^{1}$$
-CO-NR²R³ (II)

b) Harnstoffderivate der allgemeinen Formel (III)

$$R^1R^3N-CO-NR^2R^4$$
 (III)


c) Carbonate der allgemeinen Formel (IV)

$$R^{1}O-CO-OR^{2}$$
 (IV)

d) Nitroalkane der allgemeinen Formel (V)

$$R^6$$
-NO₂ (V)

e) Nitrile der allgemeinen Formel (VI)



$$\begin{bmatrix}
R^{1} & R^{3} \\
C & A & C & C \\
R^{2} & R^{4}
\end{bmatrix}$$
(XII)

- in der R^1 , R^2 , R^3 und R^4 die in Formel (Ia), Anspruch 1, zugewiesenen Bedeutungen haben, wobei ihr Molekulargewicht (M_w) > $2 \cdot 10^6$ ist.
 - 5. Polymer gemäß Anspruch 4 mit Grundeinheiten der allgemeinen Formel (XIIa)

$$\begin{bmatrix}
P & H \\
C & A & C
\end{bmatrix}$$
(XIIa)

25 in der

15

20

30

40

45

50

55

- P -SO-R⁵, SO₂-R⁵, SR⁵, OR⁵, Cl, Br, CN oder -CO-OR⁵ ist;
- R⁵ eine geradkettige oder verzweigte C₁-C₁₂-Alkylgruppe, Phenyl oder Benzyl ist und
- A die in Formel (Ia), Anspruch 1, zugewiesene Bedeutung hat, wobei das Molekulargewicht (M_w) von A > 2·10⁶ ist
- 6. Verwendung eines Polymers, das durch ein Verfahren gemäß einem oder mehreren der Ansprüche 1 bis 3 hergestellt werden kann, als Zwischenprodukt für die Herstellung elektrolumineszenter Materialien.
 - 7. Verfahren zur Herstellung konjugierter Polymere, umfassend
 - a) die Umsetzung einer Verbindung der allgemeinen Formel (Ib)

$$R^{1} - C - A - C - R^{3}$$
 (1b)

- in der
 - A, L, R¹ und R³ die in Formel (la), Anspruch 1, zugewiesene Bedeutung haben;
- P -SR⁵, -OR⁵, OH, -CI, -Br, -SO-R⁵, -SO₂-R⁵, CN oder -CO-OR⁵ ist und
 - eine geradkettige oder verzweigte C₁-C₁₂-Alkyl-, Phenyl- oder Benzyl-gruppe ist, und einer Base in einem Lösungsmittel, das eine aus der folgenden Gruppe ausgewählte Verbindung

ist:

	a) Amide der allgemeinen Formel (II)	
5	R¹-CO-NR²R³ •	(II)
•	b) Harnstoffderivate der allgemeinen Formel (III)	
10	R^1R^3N -CO-NR $^2R^4$ ((111)
	c) Carbonate der allgemeinen Formel (IV)	
15	R ¹ O-CO-OR ² ((IV)
,	d) Nitroalkane der allgemeinen Formel (V)	
20	R ⁶ -NO ₂	(V)
	e) Nitrile der allgemeinen Formel (VI)	
25	R ⁶ -CN ((VI)
	f) Amine der allgemeinen Formel (VII)	
30	R ⁵ ₂ -N-R ⁶ (\	VII)
	g) Sulfone der allgemeinen Formel (VIII)	
35	R^6 - SO_2 - R^6 (V	/III)
40	h) Sulfoxide der allgemeinen Formel (IX)	
	R ⁶ -SO-R ⁶ ((IX)
	i) Phosphoramide der allgemeinen Formel (X)	
45.	(((R ⁶) ₂)N) ₃ -P=O	(X)
50	j) Sulfonate der allgemeinen Formel (XI)	•
	R ⁶ -SO ₂ -O-R ⁶ ((XI)
	wobei in den Formeln (II) bis (XI)	
55	R ¹ , R ² , R ³ und R ⁴ unabhängig voneinander, für H oder eine geradkettige oder verzweigte Alkylgruppe s hen oder R ¹ und R ² zusammen -(CH ₂) ₂ -, -(CH ₂) ₃ - oder - (CH ₂) ₄ -sind und	ste-

- die gleiche Bedeutung hat wie R¹ oder eine Phenylgruppe oder eine durch Halogen-, Methyl- und Methoxygruppen substituierte Phenyl-gruppe ist;
- R6 die R5 zugewiesenen Bedeutungen hat, mit Ausnahme von H;

wobei ein in dem genannten Lösungsmittel weitgehend lösliches Polymer und als Nebenprodukt ein in dem genannten Lösungsmittel weitgehend unlöslicher Feststoff entstehen,

- b) wahlweise Abtrennung des genannten Polymers und
- c) Behandlung des genannten Polymers unter Bedingungen, die zur Entfernung von HP führen (wobei P die in Formel (lb) zugewiesene Bedeutung hat), so daß ein konjugiertes Polymer entsteht.
- 8. Polymer mit Grundeinheiten der allgemeinen Formel (XIII)
 - [A-CH=CH-] (XIII)
 - in der A die in Formel (Ia), Anspruch 1, zugewiesene Bedeutung hat und wobei das Molekulargewicht (M_w) von A > 2·10⁶ ist
- 9. Elektrolumineszente Vorrichtung, umfassend ein Polymer, das mit dem Verfahren gemäß Anspruch 7 hergestellt werden kann, oder ein Polymer gemäß Anspruch 8.

Revendications

5

10

15

20

25

30

35


40

45

50

55

 Procédé de production de polymères de composés conjugués insaturés en α,ω, qui comprend la réaction d'un monomère précurseur de formule (la)



dans laquelle

- R1 et R2 sont chacun indépendamment -H, -R5, -OR5, -COOR5, NO₂, -NR5R6, -SR5, CN, -SO-R5 ou -SO₂-R5, R3 et R4 sont chacun indépendamment -H, -R5, -OR5, -COOR5, NO₂, -NR5R6, -SR5, CN, -SO-R5, -SO₂-R5 ou -L,
- R⁵ et R⁶ sont chacun indépendamment un groupe alkyle en C₁-C₂₀, phényle, qui peut être mono- ou disubstitué par R¹, ou benzyle, ou bien R⁵ et R⁶ forment ensemble un groupe -(CH₂)₄- ou -(CN₂)₅-, et est CI, Br, I, -O-Tos, -O-Mes, -O-triflate, (NR⁵₃)[⊕], -(SR⁵R⁶)[⊕] ou -OOC-R⁵,
- est Cl, Br, I, -O-Tos, -O-Mes, -O-triflate, (NR⁵₃)[©], -(SR⁵R⁵)[©] ou -OOC-H⁵,

 est un groupe p-phénylène, 2,6-naphtalènediyle, 1,4-naphtalènediyle, 1,4-anthracènediyle, 2,6-anthracènediyle, 9,10-anthracènediyle, 2,5-thiénylène, 2,5-furannediyle, 2,5-pyrrolediyle, 1,3,4-oxadiazole-2,5-diyle, 1,3,4-thiadiazole-2,5-diyle, 1,3-benzo[c]furannediyle, 1,3-benzo[c]pyrrolediyle, 1,3-benzo[c]thiénylène, thiéno-[3,2-b]thiophène-2,5-diyle ou pyrrolo[3,2-b]pyrrole-2,5-diyle où les atomes H sur les poyaux aromatiques peuvent être substitués par des groupes hydrocarbonés linéaires
 - 1,3-benzo[c]thiénylène, thiéno-[3,2-b]thiophène-2,5-diyle ou pyrrolo[3,2-b]pyrrole-2,5-diyle où les atomes H sur les noyaux aromatiques peuvent être substitués par des groupes hydrocarbonés linéaires ou ramifiés ayant 1 à 22 atomes de carbone et des groupes alcoxy linéaires ou ramifiés ayant 1 à 22 atomes de carbone, des atomes d'halogène ou des groupes cyano, nitro ou ester,

avec une base dans un solvant, ledit procédé étant caractérisé en ce que, par réaction de la base avec le composé de formule (la), il se forme un polymère qui est essentiellement soluble dans ledit solvant et il se forme comme

sous-produit un solide qui est essentiellement insoluble dans ledit solvant et **en ce que** le solvant comprend un composé choisi dans la classe formée par

a) les amides de formule générale (II) R1-CO-NR2R3 (II)b) les dérivés d'urée de formule générale (III) 10 R¹R³N-CO-NR²R⁴ (III)c) les carbonates de formule générale (IV) 15 R¹O-CO-OR² (IV) d) les nitroalcanes de formule générale (V) 20 R⁶-NO₂ (V) e) les nitriles de formule générale (VI) 25 R6-CN (VI) f) les amines de formule générale (VII) 30 R⁵₂-N-R⁶ (VII) g) les sulfones de formule générale (VIII) R6-SO2-R6 (VIII) h) les sulfoxydes de formule générale (IX) 40 R⁶-SO-R⁶ (IX) i) les phosphoramides de formule générale (X) 45 $((R^6)_2N)_3$ -P=O (X) j) les sulfonates de formule générale (XI) 50 R⁶-SO₂-O-R⁶ (XI) formules (II) à (XI) dans lesquelles 55

représentent chacun, indépendamment des autres, H ou un groupe alkyle à chaîne droite ou ramifiée, ou bien R^1 et R^2 forment ensemble un groupe - $(CH_2)_2$ -, - $(CH_2)_3$ - ou - $(CH_2)_4$ -, et

R1, R2, R3 et R4

- R5 a la même définition que R1 ou est un groupe phényle ou un groupe phényle substitué par des substituants halogéno, méthyle et méthoxy,
- R⁶ a la même définition que R⁵, à l'exception de H.
- 2. Procédé selon la revendication 1, caractérisé en ce que le solvant comprend un composé de formule (IIa),

dans laquelle

10

20

25

30

35

40

45

50

R¹ et R² sont tels que définis pour la formule (II) dans la revendication 1.


- Procédé selon la revendication 1 ou 2, caractérisé en ce qu'on ajoute au mélange réactionnel un sel qui est soluble dans le solvant et qui a le même cation que la base.
 - 4. Polymère comprenant des motifs récurrents de formule générale (XII)

$$\begin{bmatrix} R^{1} & R^{3} \\ C - A - C - \\ R^{2} & R^{4} \end{bmatrix}$$
 (X11)

dans laquelle

 R^1 , R^2 , R^3 et R^4 sont tels que définis pour la formule (la) dans la revendication 1, ayant un poids moléculaire M_p supérieur à 2.10⁶.

5. Polymère selon la revendication 4, comprenant des motifs récurrents de formule générale (XIIa)



dans laquelle

P est -SO-R 5 , SO $_2$ -R 5 , SR 5 , OR 5 , CI, Br, CN ou -CO-OR 5 ,

R⁵ est un groupe alkyle en C₁-C₁₂ à chaîne droite ou ramifiée, phényle ou benzyle, et

A est tel que défini pour la formule (la) dans la revendication 1,

ayant un poids moléculaire M_p supérieur à 2.106.

- Utilisation d'un polymère pouvant être obtenu par un procédé selon l'une ou plusieurs des revendications 1 à 3, comme intermédiaire pour la production de substances électroluminescentes.
- 7. Procédé de production de polymères conjugués, qui comprend
 - a) la réaction d'un composé de formule générale (lb)

$$R^{1} - C - A - C - R^{3}$$
 (1b)

dans laquelle

10

15

30

35

40

45.

50

A, L, R^1 et R^3 sont tels que définis pour la formule (la) dans la revendication 1, est -SR⁵, -OR⁵, OH, -CI, -Br, -SO-R⁵, -SO₂-R⁵, CN ou - CO-OR⁵, et est un groupe alkyle en C_1 - C_{12} à chaîne droite ou ramifiée, phényle, benzyle,

et d'une base, dans un solvant comprenant un composé choisi dans la classe formée par .

a) les amides de formule générale (II)

$$R^{1}$$
-CO-NR 2 R 3 (II)

b) les dérivés d'urée de formule générale (III)

$$R^1R^3N$$
-CO- NR^2R^4 (III)

c) les carbonates de formule générale (IV)

d) les nitroalcanes de formule générale (V)

$$R^6-NO_2$$
 (V)

e) les nitriles de formule générale (VI)

f) les amines de formule générale (VII)

$$R_{2}^{5}-N-R^{6}$$
 (VII)

g) les sulfones de formule générale (VIII)

$$R^6$$
-SO₂- R^6 (VIII)

h) les sulfoxydes de formule générale (IX)

$$\mathsf{R}^{\mathsf{G}} ext{-}\mathsf{SO-}\mathsf{R}^{\mathsf{G}}$$
 (IX)

i) les phosphoramides de formule générale (X)

$$((R^6)_2N)_3$$
-P=O (X)

5

i) les sulfonates de formule générale (XI)

$$R^6$$
-SO₂-O-R⁶ (XI)

10

15

formules (II) à (XI) dans lesquelles

R1, R2, R3 et R4

représentent chacun, indépendamment des autres, H ou un groupe alkyle à chaîne droite ou ramifiée, ou bien R^1 et R^2 forment ensemble un groupe - $(CH_2)_2$ -, - $(CH_2)_3$ - ou - $(CH_2)_4$ -,

et

R5

a la même définition que R1 ou est un groupe phényle ou un groupe phényle substitué par des substituants halogéno, méthyle et méthoxy,

R6

a la même définition que R5, à l'exception de H,

20

par laquelle il se forme un polymère qui est essentiellement soluble dans ledit solvant, et il se forme un sous-produit solide qui est essentiellement insoluble dans ledit solvant,

- b) facultativement l'isolement dudit polymère, et
- c) le traitement dudit polymère dans des conditions provoquant l'élimination de HP (P ayant la signification donnée pour la formule (lb)), pour former ainsi un polymère conjugué.

25

Polymère comprenant des motifs récurrents de formule générale (XIII),

30

dans laquelle

A est tel que défini pour la formule (la) dans la revendication 1, ayant une masse moléculaire Mp supérieure à 2.106.

35

Dispositif électroluminescent, comprenant un polymère pouvant être obtenu par un procédé selon la revendication 7 ou un polymère selon la revendication 8.

40

45

50

55